

View Online at <https://aerobasegroup.com/nsn/5999-00-806-8746>

Body Style:

Rectangular

Frequency Rating:

Not rated

Body Length:

6.000 inches

Body Width:

2.000 inches

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

1.500 inches

Longest Vertical Distance Between Mounting Centers:

5.500 inches

Operating Temperature Range:

-20.0/+85.0 degrees celsius

Stud Length:

0.500 inches

Mounting Facility Quantity:

4

Voltage Rating:

Not rated

Material And Location:

Metal

Surface Treatment And Location:

Any acceptable

Input Impedance Rating:

2.000 kilohms

Output Impedance Rating:

1.000 kilohms

Frequency Bandwidth:

Not rated

Body Depth:

4.000 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

50.000

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

15.200 microseconds 2nd section err-100

Segment Quantity Per Section:

17 2nd section

Segment Delay Time:

8.800 microseconds 2nd section 1st segment err-100

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

700.0 nanoseconds

Terminal Type And Quantity:

10 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100