

View Online at <https://aerobasegroup.com/nsn/5999-00-806-8746>

**Body Style:**

Rectangular

**Frequency Rating:**

Not rated

**Body Length:**

6.000 inches

**Body Width:**

2.000 inches

**Individual Section Quantity:**

2

**Longest Horizontal Distance Between Mounting Centers:**

1.500 inches

**Longest Vertical Distance Between Mounting Centers:**

5.500 inches

**Operating Temperature Range:**

-20.0/+85.0 degrees celsius

**Stud Length:**

0.500 inches

**Mounting Facility Quantity:**

4

**Voltage Rating:**

Not rated

**Material And Location:**

Metal

**Surface Treatment And Location:**

Any acceptable

**Input Impedance Rating:**

2.000 kilohms

**Output Impedance Rating:**

1.000 kilohms

**Frequency Bandwidth:**

Not rated

**Body Depth:**

4.000 inches

**Mounting Facility:**

Threaded stud

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

50.000

**Signal Delay Method:**

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

15.200 microseconds 2nd section err-100

Segment Quantity Per Section:

17 2nd section

Segment Delay Time:

8.800 microseconds 2nd section 1st segment err-100

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

700.0 nanoseconds

Terminal Type And Quantity:

10 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100