

View Online at <https://aerobasegroup.com/nsn/5999-00-806-8746>

**Body Style:**

Rectangular

**Frequency Rating:**

Not rated

**Body Length:**

6.000 inches

**Body Width:**

2.000 inches

**Individual Section Quantity:**

2

**Longest Horizontal Distance Between Mounting Centers:**

1.500 inches

**Longest Vertical Distance Between Mounting Centers:**

5.500 inches

**Operating Temperature Range:**

-20.0/+85.0 degrees celsius

**Stud Length:**

0.500 inches

**Mounting Facility Quantity:**

4

**Voltage Rating:**

Not rated

**Material And Location:**

Metal

**Surface Treatment And Location:**

Any acceptable

**Input Impedance Rating:**

2.000 kilohms

**Output Impedance Rating:**

1.000 kilohms

**Frequency Bandwidth:**

Not rated

**Body Depth:**

4.000 inches

**Mounting Facility:**

Threaded stud

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

50.000

**Signal Delay Method:**

Lumped constant

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

15.200 microseconds 2nd section err-100

**Segment Quantity Per Section:**

17 2nd section

**Segment Delay Time:**

8.800 microseconds 2nd section 1st segment err-100

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

700.0 nanoseconds

**Terminal Type And Quantity:**

10 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100