NSN 5999-00-812-3349



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-812-3349 **Thread Class:** 2a **Body Style:** Rectangular **Body Length:** 3.750 inches **Body Width:** 3.310 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 2.063 inches **Longest Vertical Distance Between Mounting Centers:** 2.563 inches Stud Length: 0.470 inches **Mounting Facility Quantity: Material And Location:** Steel **Surface Treatment And Location:** Tin plated terminal err-100 err-100 Input Impedance Rating: 2.200 kilohms **Output Impedance Rating:** 2.200 kilohms **Body Depth:** 2.810 inches Step Quantity: 4 **Mounting Facility:** Threaded stud **Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** 3.000 **Signal Delay Method:** Inductance **Delay Time Variation Method:**

Adjustable

Section Delay Time:

14.000 microseconds single section

NSN 5999-00-812-3349

Delay Line - Page 2 of 2



Pulse Rise Time Rating:
420.0 nanoseconds
Terminal Type And Quantity:
14 wire hook
Thread Size And Series/type Designator:
0.164-32 unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A32100