

View Online at <https://aerobasegroup.com/nsn/5999-00-812-6869>

**Thread Class:**

2a

**Body Style:**

Rectangular

**Frequency Rating:**

Not rated

**Body Length:**

3.500 inches

**Body Width:**

1.875 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

3.000 inches

**Operating Temperature Range:**

-20.0/+85.0 degrees celsius

**Stud Length:**

0.312 inches

**Mounting Facility Quantity:**

2

**Voltage Rating:**

Not rated

**Material And Location:**

Metal

**Surface Treatment And Location:**

Any acceptable

**Input Impedance Rating:**

10.000 kilohms

**Output Impedance Rating:**

10.000 kilohms

**Frequency Bandwidth:**

Not rated

**Body Depth:**

0.594 inches

**Mounting Facility:**

Threaded stud

**Mounting Provision Arrangement Style:**

2 position in-line

**Attenuation In Decibels:**

Not rated

**Signal Delay Method:**

Inductance

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

5.900 microseconds single section

**Segment Quantity Per Section:**

6 single section

**Segment Delay Time:**

500.000 nanoseconds single section 1st segment err-100

**Delay Time Variation Per Deg Celsius:**

120.000 nanoseconds

**Pulse Rise Time Rating:**

500.0 nanoseconds

**Terminal Type And Quantity:**

8 tab solder lug

**Thread Size And Series/type Designator:**

0.138-32 unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100