

View Online at <https://aerobasegroup.com/nsn/5999-00-815-0524>

Thread Class:

2a

Thread Pitch Diameters:

+0.1875/+0.1876 inches

Body Style:

Rectangular

Body Length:

1.000 inches

Body Width:

2.063 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.500 inches

Longest Vertical Distance Between Mounting Centers:

0.650 inches

Stud Length:

0.375 inches

Mounting Facility Quantity:

2

Material And Location:

Any acceptable

Surface Treatment And Location:

Any acceptable

Input Impedance Rating:

330.000 kilohms

Output Impedance Rating:

330.000 kilohms

Body Depth:

1.000 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

2 position diagonal

Attenuation In Decibels:

0.500

Signal Delay Method:

Lumped constant

Section Delay Time:

5.000 microseconds single section

Pulse Rise Time Rating:

1.3 microseconds

Terminal Type And Quantity:

3 tab solder lug

Thread Size And Series/type Designator:

0.138-32 unc

Fsc Application Data:

Radar nonairborne except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100