

View Online at <https://aerobasegroup.com/nsn/5999-00-815-0524>

**Thread Class:**

2a

**Thread Pitch Diameters:**

+0.1875/+0.1876 inches

**Body Style:**

Rectangular

**Body Length:**

1.000 inches

**Body Width:**

2.063 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

0.500 inches

**Longest Vertical Distance Between Mounting Centers:**

0.650 inches

**Stud Length:**

0.375 inches

**Mounting Facility Quantity:**

2

**Material And Location:**

Any acceptable

**Surface Treatment And Location:**

Any acceptable

**Input Impedance Rating:**

330.000 kilohms

**Output Impedance Rating:**

330.000 kilohms

**Body Depth:**

1.000 inches

**Mounting Facility:**

Threaded stud

**Mounting Provision Arrangement Style:**

2 position diagonal

**Attenuation In Decibels:**

0.500

**Signal Delay Method:**

Lumped constant

**Section Delay Time:**

5.000 microseconds single section

**Pulse Rise Time Rating:**

1.3 microseconds

**Terminal Type And Quantity:**

3 tab solder lug

**Thread Size And Series/type Designator:**

0.138-32 unc

**Fsc Application Data:**

Radar nonairborne except fire control and guided missile

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100