

View Online at <https://aerobasegroup.com/nsn/5999-00-815-0526>

**Thread Class:**

2a

**Body Style:**

Rectangular

**Body Length:**

3.000 inches

**Body Width:**

1.310 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

0.813 inches

**Longest Vertical Distance Between Mounting Centers:**

0.813 inches

**Operating Temperature Range:**

-55.0 to 125.0 degrees celsius

**Stud Length:**

0.470 inches

**Mounting Facility Quantity:**

4

**Material And Location:**

Steel case

**Surface Treatment And Location:**

Enamel, dull gray, metallic case

**Input Impedance Rating:**

1.000 kilohms

**Output Impedance Rating:**

1.000 kilohms

**Frequency Bandwidth:**

600.0 kilohertz

**Body Depth:**

1.310 inches

**Mounting Facility:**

Threaded stud

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

6.000

**Signal Delay Method:**

Lumped constant

**Section Delay Time:**

10.000 microseconds single section

**Pulse Rise Time Rating:**

600.0 nanoseconds

**Terminal Type And Quantity:**

3 tab solder lug

**Thread Size And Series/type Designator:**

0.138-32 unc

**Fsc Application Data:**

Radar set nonairborne except fire control and guided missile

**Reference Number Differentiating Characteristics:**

As modified by westinghouse dwg 342c443h07

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A32100