

View Online at <https://aerobasegroup.com/nsn/5999-00-815-0526>

Thread Class:

2a

Body Style:

Rectangular

Body Length:

3.000 inches

Body Width:

1.310 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.813 inches

Longest Vertical Distance Between Mounting Centers:

0.813 inches

Operating Temperature Range:

-55.0 to 125.0 degrees celsius

Stud Length:

0.470 inches

Mounting Facility Quantity:

4

Material And Location:

Steel case

Surface Treatment And Location:

Enamel, dull gray, metallic case

Input Impedance Rating:

1.000 kilohms

Output Impedance Rating:

1.000 kilohms

Frequency Bandwidth:

600.0 kilohertz

Body Depth:

1.310 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

6.000

Signal Delay Method:

Lumped constant

Section Delay Time:

10.000 microseconds single section

Pulse Rise Time Rating:

600.0 nanoseconds

Terminal Type And Quantity:

3 tab solder lug

Thread Size And Series/type Designator:

0.138-32 unc

Fsc Application Data:

Radar set nonairborne except fire control and guided missile

Reference Number Differentiating Characteristics:

As modified by westinghouse dwg 342c443h07

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A32100