

View Online at <https://aerobasegroup.com/nsn/5999-00-820-8711>

**Thread Class:**

2a

**Body Style:**

Rectangular

**Body Length:**

3.750 inches

**Body Width:**

1.880 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

0.136 inches

**Longest Vertical Distance Between Mounting Centers:**

0.112 inches

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Stud Length:**

0.470 inches

**Mounting Facility Quantity:**

4

**Material And Location:**

Steel case

**Surface Treatment And Location:**

Lacquer, gray case

**Input Impedance Rating:**

500.000 ohms

**Output Impedance Rating:**

500.000 ohms

**Body Depth:**

1.630 inches

**Mounting Facility:**

Threaded stud

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

6.000

**Signal Delay Method:**

Lumped constant

**Section Delay Time:**

25.000 microseconds single section

**Terminal Type And Quantity:**

3 tab solder lug

**Test Data Document:**

10001-1088810 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Size And Series/type Designator:**

0.138-32 unc

**Fsc Application Data:**

Fire control designating and indicating equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100