

View Online at <https://aerobasegroup.com/nsn/5999-00-820-8711>

Thread Class:

2a

Body Style:

Rectangular

Body Length:

3.750 inches

Body Width:

1.880 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.136 inches

Longest Vertical Distance Between Mounting Centers:

0.112 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Stud Length:

0.470 inches

Mounting Facility Quantity:

4

Material And Location:

Steel case

Surface Treatment And Location:

Lacquer, gray case

Input Impedance Rating:

500.000 ohms

Output Impedance Rating:

500.000 ohms

Body Depth:

1.630 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

6.000

Signal Delay Method:

Lumped constant

Section Delay Time:

25.000 microseconds single section

Terminal Type And Quantity:

3 tab solder lug

Test Data Document:

10001-1088810 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Size And Series/type Designator:

0.138-32 unc

Fsc Application Data:

Fire control designating and indicating equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100