

View Online at <https://aerobasegroup.com/nsn/5999-00-840-3377>

Body Style:

Rectangular, bracketed

Hole Diameter:

0.188 inches

Overall Length:

4.250 inches

Flat Height:

0.188 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.312 inches

Flatted Portion Length:

0.312 inches

Adjustment Device Quantity:

2

Adjustment Device Drive Type:

Shaft

Body Length:

3.250 inches

Body Width:

3.500 inches

Shaft Style:

Round, flatted

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

3.750 inches

Longest Vertical Distance Between Mounting Centers:

1.750 inches

Operating Temperature Range:

+0.0/+75.0 degrees celsius

Mounting Facility Quantity:

4

Material And Location:

Steel case

Surface Treatment And Location:

Enamel, dull gray, metallic case

Input Impedance Rating:

500.000 ohms

Output Impedance Rating:

500.000 ohms

Frequency Bandwidth:

900.0 kilohertz

Body Depth:

2.250 inches

Step Quantity:

10

Mounting Facility:

Unthreaded hole

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

4.000

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Adjustable

Delay Time Per Step:

70.000 nanoseconds

Section Delay Time:

7.000 microseconds single section

Pulse Rise Time Rating:

400.0 nanoseconds

Terminal Type And Quantity:

2 connector, receptacle and 2 tab solder lug

Special Features:

Fine control 11 equal increments 0/0.7 microsecond each

Fsc Application Data:

Radar nonairborne except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100