

View Online at <https://aerobasegroup.com/nsn/5999-00-845-8685>

Thread Class:

2a

Thread Pitch Diameters:

+0.1875/+0.1876 inches

Body Style:

Rectangular

Body Length:

3.000 inches

Body Width:

1.310 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.813 inches

Longest Vertical Distance Between Mounting Centers:

0.813 inches

Stud Length:

0.470 inches

Mounting Facility Quantity:

4

Material And Location:

Steel case

Surface Treatment And Location:

Enamel coating over zinc coating case

Input Impedance Rating:

100.000 ohms

Output Impedance Rating:

100.000 ohms

Body Depth:

1.310 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

1.500

Signal Delay Method:

Lumped constant

Section Delay Time:

1.000 microseconds single section

Terminal Type And Quantity:

3 wire hook

Thread Size And Series/type Designator:

0.138-32 unc

Fsc Application Data:

Radar nonairborne except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100