

View Online at <https://aerobasegroup.com/nsn/5999-00-847-3721>

Thread Class:

2a

Thread Pitch Diameters:

+0.0312/+0.0313 inches

Body Style:

Rectangular

Slot Depth:

0.130 inches

Slot Width:

0.050 inches

Shaft Diameter:

0.250 inches

Bushing Length:

0.440 inches

Shaft Length:

0.690 inches

Adjustment Device Quantity:

1

Adjustment Device Drive Type:

Shaft

Body Length:

7.250 inches

Body Width:

1.630 inches

Shaft Style:

Round, slotted

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

6.500 inches

Stud Length:

0.470 inches

Mounting Facility Quantity:

1 and 2

Material And Location:

Steel

Surface Treatment And Location:

Enamel body

Input Impedance Rating:

180.000 ohms

Output Impedance Rating:

180.000 ohms

Body Depth:

1.000 inches

Mounting Facility:

Threaded bushing and threaded stud

Mounting Provision Arrangement Style:

2 position in-line

Attenuation In Decibels:

3.000

Signal Delay Method:

Electromechanical

Delay Time Variation Method:

Tapped

Section Delay Time:

6.000 microseconds single section

Segment Quantity Per Section:

1 single section

Segment Delay Time:

300.000 nanoseconds single section 1st segment

Pulse Rise Time Rating:

1.2 microseconds

Terminal Type And Quantity:

4 wire hook

Thread Size And Series/type Designator:

0.375-32 unef and 0.164-32 unc

Fsc Application Data:

Radar set, guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A32100