NSN 5999-00-849-5107



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-849-5107 **Body Style:** Rectangular, bracketed **Hole Diameter:** 0.136 inches **Overall Length:** 4.000 inches **Body Length:** 3.250 inches **Body Width:** 1.000 inches **Individual Section Quantity:** 12 **Longest Horizontal Distance Between Mounting Centers:** 3.625 inches **Longest Vertical Distance Between Mounting Centers:** 0.375 inches **Operating Tempurature Range:** -55.0/+110.0 degrees celsius **Mounting Facility Quantity: Material And Location:** Any acceptable **Surface Treatment And Location:** Any acceptable Input Impedance Rating: 600.000 ohms **Output Impedance Rating:** 600.000 ohms Frequency Bandwidth: 180.0 kilohertz **Body Depth:** 0.750 inches **Mounting Facility: Bracket Mounting Provision Arrangement Style:** 2 position diagonal **Signal Delay Method:**

Lumped constant

Section Delay Time:

1.000 microseconds all sections

Pulse Rise Time Rating:

2.0 microseconds

NSN 5999-00-849-5107

Delay Line - Page 2 of 2



| Terminal Type A | and Quantity | / : |
|-----------------|--------------|------------|
|-----------------|--------------|------------|

3 tab solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100