

View Online at <https://aerobasegroup.com/nsn/5999-00-852-0551>

Thread Class:

2a

Thread Pitch Diameters:

+0.1380/+0.1390 inches

Body Style:

Rectangular

Body Length:

3.000 inches

Body Width:

1.880 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.125 inches

Longest Vertical Distance Between Mounting Centers:

1.375 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Stud Length:

0.500 inches

Mounting Facility Quantity:

4

Voltage Rating:

500.000 pounds per hour wet

Material And Location:

Steel

Surface Treatment And Location:

Enamel

Input Impedance Rating:

2.000 kilohms

Output Impedance Rating:

2.000 kilohms

Body Depth:

1.630 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

6.000

Signal Delay Method:

Lumped constant

Section Delay Time:

25.000 microseconds single section

Pulse Rise Time Rating:

1.8 microseconds

Terminal Type And Quantity:

3 wire hook

Thread Size And Series/type Designator:

0.138-32 unc

Fsc Application Data:

Radar set, guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A32100