

View Online at <https://aerobasegroup.com/nsn/5999-00-855-5936>

**Thread Class:**

2b

**Thread Pitch Diameters:**

+0.1141/+0.1169 inches

**Body Style:**

Rectangular, front connection

**Overall Depth:**

1.500 inches

**Frequency Rating:**

Not rated

**Body Length:**

3.500 inches

**Body Width:**

2.250 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

3.000 inches

**Longest Vertical Distance Between Mounting Centers:**

1.750 inches

**Operating Temperature Range:**

-40.0/+175.0 degrees fahrenheit

**Mounting Facility Quantity:**

4

**Voltage Rating:**

Not rated

**Material And Location:**

Any acceptable

**Input Impedance Rating:**

200.000 ohms

**Output Impedance Rating:**

Not rated

**Frequency Bandwidth:**

Not rated

**Body Depth:**

1.250 inches

**Mounting Facility:**

Threaded hole

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

1.000

**Signal Delay Method:**

Electromechanical

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

1.000 microseconds single section

**Segment Quantity Per Section:**

8 single section

**Segment Delay Time:**

42.000 nanoseconds single section 8th segment err-100

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

38.000 nanoseconds

**Terminal Type And Quantity:**

11 wire hook

**Test Data Document:**

19200-10548197 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Size And Series/type Designator:**

0.138-32 unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100