

View Online at <https://aerobasegroup.com/nsn/5999-00-855-5936>

Thread Class:

2b

Thread Pitch Diameters:

+0.1141/+0.1169 inches

Body Style:

Rectangular, front connection

Overall Depth:

1.500 inches

Frequency Rating:

Not rated

Body Length:

3.500 inches

Body Width:

2.250 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

3.000 inches

Longest Vertical Distance Between Mounting Centers:

1.750 inches

Operating Temperature Range:

-40.0/+175.0 degrees fahrenheit

Mounting Facility Quantity:

4

Voltage Rating:

Not rated

Material And Location:

Any acceptable

Input Impedance Rating:

200.000 ohms

Output Impedance Rating:

Not rated

Frequency Bandwidth:

Not rated

Body Depth:

1.250 inches

Mounting Facility:

Threaded hole

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

1.000

Signal Delay Method:

Electromechanical

Delay Time Variation Method:

Tapped

Section Delay Time:

1.000 microseconds single section

Segment Quantity Per Section:

8 single section

Segment Delay Time:

42.000 nanoseconds single section 8th segment err-100

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

38.000 nanoseconds

Terminal Type And Quantity:

11 wire hook

Test Data Document:

19200-10548197 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Size And Series/type Designator:

0.138-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100