## NSN 5999-00-855-9074

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-855-9074

Thread Class:
2a
Frequency Rating:
Not rated
Adjustment Device Quantity:
1
Adjustment Device Drive Type:
Shaft
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
Mounting Facility Quantity:
1
Voltage Rating:
Not rated
Input Impedance Rating:
620.000 ohms
Output Impedance Rating:
620.000 ohms
Frequency Bandwidth:
18000.0 kilohertz
Mounting Facility:
Threaded bushing
Attenuation In Decibels:
Not rated
Delay Time Variation Method:
Variable
Section Delay Time:
100.000 nanoseconds single section err-100
Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
35.0 nanoseconds
Terminal Type And Quantity:
4 solder stud
Thread Size And Series/type Designator:
0.375-32 unef
Fsc Application Data:
Radar sets, airborne, except fire control and guided missile
Shelf Life:
N/a
Unit Of Measure:
<del></del>

## NSN 5999-00-855-9074

Delay Line - Page 2 of 2



Demilitarization:

No

Fiig:

A32100