NSN 5999-00-856-7712

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-856-7712

Thread Class:
2b
Thread Pitch Diameters:
+0.2800/+0.2801 inches
Body Style:
Rectangular
Body Length:
1.421 inches
Body Width:
1.231 inches
Individual Section Quantity:
1
Longest Horizontal Distance Between Mounting Centers:
0.750 inches
Longest Vertical Distance Between Mounting Centers:
0.937 inches
Mounting Facility Quantity:
2
Material And Location:
Any acceptable
Surface Treatment And Location:
Any acceptable
Frequency Bandwidth:
2570.0 kilohertz
Body Depth:
0.625 inches
Mounting Facility:
Mounting Facility: Threaded hole
Threaded hole
Threaded hole Mounting Provision Arrangement Style:
Threaded hole Mounting Provision Arrangement Style: 2 position diagonal
Threaded hole Mounting Provision Arrangement Style: 2 position diagonal Signal Delay Method:
Threaded hole Mounting Provision Arrangement Style: 2 position diagonal Signal Delay Method: Lumped constant
Threaded hole Mounting Provision Arrangement Style: 2 position diagonal Signal Delay Method: Lumped constant Section Delay Time:
Threaded hole Mounting Provision Arrangement Style: 2 position diagonal Signal Delay Method: Lumped constant Section Delay Time: 175.000 nanoseconds single section
Threaded hole Mounting Provision Arrangement Style: 2 position diagonal Signal Delay Method: Lumped constant Section Delay Time: 175.000 nanoseconds single section Pulse Rise Time Rating:
Threaded hole Mounting Provision Arrangement Style: 2 position diagonal Signal Delay Method: Lumped constant Section Delay Time: 175.000 nanoseconds single section Pulse Rise Time Rating: 20.0 nanoseconds
Threaded hole Mounting Provision Arrangement Style: 2 position diagonal Signal Delay Method: Lumped constant Section Delay Time: 175.000 nanoseconds single section Pulse Rise Time Rating: 20.0 nanoseconds Terminal Type And Quantity:
Threaded hole Mounting Provision Arrangement Style: 2 position diagonal Signal Delay Method: Lumped constant Section Delay Time: 175.000 nanoseconds single section Pulse Rise Time Rating: 20.0 nanoseconds Terminal Type And Quantity: 5 solder stud

0.112-40 unc

NSN 5999-00-856-7712

Delay Line - Page 2 of 2



	Fsc	Ap	olication	Data:
--	-----	----	-----------	-------

Radar nonairborne except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100