

View Online at <https://aerobasegroup.com/nsn/5999-00-859-4819>

Thread Class:

2a

Body Style:

Rectangular, bracketed

Body Length:

7.100 inches

Body Width:

2.060 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.310 inches

Longest Vertical Distance Between Mounting Centers:

5.600 inches

Operating Temperature Range:

-18.0/+100.0 degrees celsius

Mounting Facility Quantity:

4

Surface Treatment And Location:

Enamel, mil-e-15090, type 3, class 2

Input Impedance Rating:

180.000 ohms

Output Impedance Rating:

180.000 ohms

Body Depth:

2.080 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

6.000

Signal Delay Method:

Inductance

Delay Time Variation Method:

Tapped

Section Delay Time:

10.550 microseconds single section

Segment Quantity Per Section:

9 single section

Segment Delay Time:

8.600 microseconds single section 8th segment err-100

Pulse Rise Time Rating:

700.0 nanoseconds

Terminal Type And Quantity:

10 wire leads

Thread Size And Series/type Designator:

0.137-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100