## NSN 5999-00-859-8349

Delay Line - Page 1 of 2

**Thread Class:** 

**Thread Pitch Diameters:** 

2a



View Online at https://aerobasegroup.com/nsn/5999-00-859-8349

+0.1177/+0.1380 inches
Body Style:
Rectangular, top connection
Frequency Rating:
1.600 megahertz
Body Length:
3.750 inches
Body Width:
1.000 inches
Individual Section Quantity:
5
Operating Tempurature Range:
+0.0/+60.0 degrees celsius
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
2
Voltage Rating:
500.000 volts
Input Impedance Rating:
100.000 ohms
Output Impedance Rating:
100.000 ohms
Frequency Bandwidth:
Not rated
Body Depth:
1.500 inches
Mounting Facility:
Threaded stud
Attenuation In Decibels:
3.000
Signal Delay Method:
Inductance
<b>Delay Time Variation Method:</b>
Tapped
Section Delay Time:
2.000 microseconds 5th section err-100
Segment Delay Time:
2.000 microseconds all sections all segments

## NSN 5999-00-859-8349

Delay Line - Page 2 of 2



Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
0.2 microseconds
Terminal Type And Quantity:
5 wire hook
Thread Size And Series/type Designator:
0.138-32 unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

**Fiig:** A32100