

View Online at <https://aerobasegroup.com/nsn/5999-00-859-8349>

Thread Class:

2a

Thread Pitch Diameters:

+0.1177/+0.1380 inches

Body Style:

Rectangular, top connection

Frequency Rating:

1.600 megahertz

Body Length:

3.750 inches

Body Width:

1.000 inches

Individual Section Quantity:

5

Operating Temperature Range:

+0.0/+60.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

2

Voltage Rating:

500.000 volts

Input Impedance Rating:

100.000 ohms

Output Impedance Rating:

100.000 ohms

Frequency Bandwidth:

Not rated

Body Depth:

1.500 inches

Mounting Facility:

Threaded stud

Attenuation In Decibels:

3.000

Signal Delay Method:

Inductance

Delay Time Variation Method:

Tapped

Section Delay Time:

2.000 microseconds 5th section err-100

Segment Delay Time:

2.000 microseconds all sections all segments

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

0.2 microseconds

Terminal Type And Quantity:

5 wire hook

Thread Size And Series/type Designator:

0.138-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100