## NSN 5999-00-864-9453



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-864-9453 **Thread Class:** 2a **Thread Pitch Diameters:** +0.1140/+0.1170 inches **Body Style:** Rectangular **Body Length:** 3.380 inches **Body Width:** 1.080 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.250 inches **Longest Vertical Distance Between Mounting Centers:** 2.630 inches **Operating Tempurature Range:** -54.0/+125.0 degrees celsius Stud Length: 0.470 inches **Mounting Facility Quantity:** 2 **Material And Location:** Any acceptable **Surface Treatment And Location:** Any acceptable Input Impedance Rating: 6.200 kilohms **Output Impedance Rating:** 6.200 kilohms Frequency Bandwidth: 110.0 kilohertz **Body Depth:** 0.770 inches **Mounting Facility:** Threaded stud **Mounting Provision Arrangement Style:** 

Four position rectangular

Signal Delay Method:

Lumped constant

Section Delay Time:

occitori Belay Time.

4.500 microseconds single section

## **NSN 5999-00-864-9453**Delay Line - Page 2 of 2



Pulse Rise Time Rating:
3.2 microseconds
Terminal Type And Quantity:
3 solder stud
Thread Size And Series/type Designator:
0.138 unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A32100