## NSN 5999-00-869-9154



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-869-9154 **Thread Class:** 2a **Body Style:** Rectangular **Body Length:** 2.125 inches **Body Width:** 1.000 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.594 inches **Longest Vertical Distance Between Mounting Centers:** 0.594 inches **Operating Tempurature Range:** +0.0/+60.0 degrees celsius Stud Length: 0.375 inches **Mounting Facility Quantity: Voltage Rating:** 30.000 volts **Surface Treatment And Location:** Enamel, mil-e-15090, type 2, class 2 body Input Impedance Rating: 500.000 ohms **Output Impedance Rating:** 500.000 ohms **Body Depth:** 1.000 inches **Mounting Facility:** Threaded stud **Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** 3.400 microseconds single section err-100

6.000 **Section Delay Time: Pulse Rise Time Rating:** 1.0 microseconds Thread Size And Series/type Designator: 0.112-40 unc

## NSN 5999-00-869-9154

Delay Line - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100