## NSN 5999-00-871-7207



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-871-7207 **Body Style:** Rectangular, top connection **Overall Width:** 1.594 inches Frequency Rating: Not rated **Body Length:** 2.375 inches **Body Width:** 1.344 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 1.375 inches **Operating Tempurature Range:** -40.0/+175.0 degrees fahrenheit **Mounting Facility Quantity:** 2 **Voltage Rating:** Not rated **Material And Location:** Any acceptable Input Impedance Rating: 100.000 ohms **Output Impedance Rating:** Not rated Frequency Bandwidth: Not rated **Body Depth:** 1.000 inches **Mounting Facility:** Unthreaded hole **Mounting Provision Arrangement Style:** 2 position in-line **Attenuation In Decibels:** 2.000 **Signal Delay Method:** Electromechanical

**Delay Time Variation Method:** Tapped

**Section Delay Time:** 

1.850 microseconds single section err-100

## NSN 5999-00-871-7207

Delay Line - Page 2 of 2

Yes - demil/mli

**Fiig:** A32100



## Segment Quantity Per Section: 4 single section Segment Delay Time: 1.900 microseconds single section 4th segment err-100 Delay Time Variation Per Deg Celsius: Not rated Pulse Rise Time Rating: 150.0 nanoseconds Terminal Type And Quantity: 6 tab solder lug Shelf Life: N/a Unit Of Measure: -- Demilitarization: