

View Online at <https://aerobasegroup.com/nsn/5999-00-878-0993>

**Body Style:**

Rectangular

**Hole Diameter:**

0.062 inches

**Frequency Rating:**

Not rated

**Body Length:**

2.500 inches

**Body Width:**

1.000 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

2.125 inches

**Shortest Horizontal Distance Between Mounting Centers:**

2.001 inches

**Intermediate Horizontal Distance Between Mounting Centers:**

1.938 inches

**Longest Vertical Distance Between Mounting Centers:**

2.125 inches

**Shortest Vertical Distance Between Mounting Centers:**

0.500 inches

**Operating Temperature Range:**

Not rated

**Inclosure Type:**

Encased

**Mounting Facility Quantity:**

4

**Voltage Rating:**

12.000 volts

**Material And Location:**

Any acceptable case

**Surface Treatment And Location:**

Any acceptable case

**Input Impedance Rating:**

250.000 ohms

**Output Impedance Rating:**

250.000 ohms

**Frequency Bandwidth:**

Not rated

**Body Depth:**

0.380 inches

**Mounting Facility:**

Unthreaded hole

**Mounting Provision Arrangement Style:**

Four position off-set

**Attenuation In Decibels:**

Not rated

**Signal Delay Method:**

Inductance

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

4.100 microseconds single section

**Segment Quantity Per Section:**

7 single section

**Segment Delay Time:**

1.050 microseconds single section 7th segment err-100

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

0.1 microseconds

**Terminal Type And Quantity:**

3 wire leads and 7 tab solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100