

View Online at <https://aerobasegroup.com/nsn/5999-00-878-0993>

Body Style:

Rectangular

Hole Diameter:

0.062 inches

Frequency Rating:

Not rated

Body Length:

2.500 inches

Body Width:

1.000 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

2.125 inches

Shortest Horizontal Distance Between Mounting Centers:

2.001 inches

Intermediate Horizontal Distance Between Mounting Centers:

1.938 inches

Longest Vertical Distance Between Mounting Centers:

2.125 inches

Shortest Vertical Distance Between Mounting Centers:

0.500 inches

Operating Temperature Range:

Not rated

Inclosure Type:

Encased

Mounting Facility Quantity:

4

Voltage Rating:

12.000 volts

Material And Location:

Any acceptable case

Surface Treatment And Location:

Any acceptable case

Input Impedance Rating:

250.000 ohms

Output Impedance Rating:

250.000 ohms

Frequency Bandwidth:

Not rated

Body Depth:

0.380 inches

Mounting Facility:

Unthreaded hole

Mounting Provision Arrangement Style:

Four position off-set

Attenuation In Decibels:

Not rated

Signal Delay Method:

Inductance

Delay Time Variation Method:

Tapped

Section Delay Time:

4.100 microseconds single section

Segment Quantity Per Section:

7 single section

Segment Delay Time:

1.050 microseconds single section 7th segment err-100

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

0.1 microseconds

Terminal Type And Quantity:

3 wire leads and 7 tab solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100