

View Online at <https://aerobasegroup.com/nsn/5999-00-880-1366>

Thread Class:

2a

Thread Pitch Diameters:

+0.1875/+0.1876 inches

Body Style:

Rectangular

Frequency Rating:

Not rated

Adjustment Device Quantity:

1

Adjustment Device Drive Type:

Slotted screw

Body Length:

5.500 inches

Body Width:

4.563 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

4.600 inches

Longest Vertical Distance Between Mounting Centers:

2.700 inches

Operating Temperature Range:

+0.0/+60.0 degrees celsius

Stud Length:

0.437 inches

Mounting Facility Quantity:

4

Voltage Rating:

Not rated

Material And Location:

Steel case

Surface Treatment And Location:

Any acceptable

Input Impedance Rating:

Not rated

Output Impedance Rating:

Not rated

Frequency Bandwidth:

3600.0 kilohertz

Body Depth:

0.500 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

Not rated

Signal Delay Method:

Inductance

Delay Time Variation Method:

Variable

Section Delay Time:

278.000 microseconds single section err-100

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

100.0 nanoseconds

Terminal Type And Quantity:

5 pin

Thread Size And Series/type Designator:

0.138-32 unc

Fsc Application Data:

Radar nonairborne except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100