

View Online at <https://aerobasegroup.com/nsn/5999-00-880-1366>

**Thread Class:**

2a

**Thread Pitch Diameters:**

+0.1875/+0.1876 inches

**Body Style:**

Rectangular

**Frequency Rating:**

Not rated

**Adjustment Device Quantity:**

1

**Adjustment Device Drive Type:**

Slotted screw

**Body Length:**

5.500 inches

**Body Width:**

4.563 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

4.600 inches

**Longest Vertical Distance Between Mounting Centers:**

2.700 inches

**Operating Temperature Range:**

+0.0/+60.0 degrees celsius

**Stud Length:**

0.437 inches

**Mounting Facility Quantity:**

4

**Voltage Rating:**

Not rated

**Material And Location:**

Steel case

**Surface Treatment And Location:**

Any acceptable

**Input Impedance Rating:**

Not rated

**Output Impedance Rating:**

Not rated

**Frequency Bandwidth:**

3600.0 kilohertz

**Body Depth:**

0.500 inches

**Mounting Facility:**

Threaded stud

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

Not rated

**Signal Delay Method:**

Inductance

**Delay Time Variation Method:**

Variable

**Section Delay Time:**

278.000 microseconds single section err-100

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

100.0 nanoseconds

**Terminal Type And Quantity:**

5 pin

**Thread Size And Series/type Designator:**

0.138-32 unc

**Fsc Application Data:**

Radar nonairborne except fire control and guided missile

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100