NSN 5999-00-892-3872

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-892-3872

view Online at https://aerobasegroup.com/hsi//3999-00-092-3072
Frequency Rating:
Not rated
Adjustment Device Quantity:
1
Adjustment Device Drive Type:
Shaft
Longest Horizontal Distance Between Mounting Centers:
5.625 inches
Operating Tempurature Range:
-0.0/+74.0 degrees celsius
Mounting Facility Quantity:
2
Voltage Rating:
Not rated
Input Impedance Rating:
500.000 ohms
Output Impedance Rating:
500.000 ohms
Frequency Bandwidth:
3000.0 kilohertz
Mounting Facility:
Threaded stud
Mounting Provision Arrangement Style:
2 position in-line
Attenuation In Decibels:
2.600
Delay Time Variation Method:
Variable
Section Delay Time:
950.000 nanoseconds single section err-100
Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
Not rated
Terminal Type And Quantity:
4 tab solder lug
Special Features:
Hermetically sealed
Thread Size And Series/type Designator:
0.138-32 unc
Fsc Application Data:
Radar sets, nonairborne, except fire control and guided missile

NSN 5999-00-892-3872

Delay Line - Page 2 of 2



-			
٠.	hΔ	Iŧ.	ife:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A32100