

View Online at <https://aerobasegroup.com/nsn/5999-00-893-0858>

Thread Class:

2a

Body Style:

Cylindrical, end post connection

Slot Depth:

0.040 inches

Slot Width:

0.030 inches

Overall Length:

4.570 inches

Body Diameter:

1.000 inches

Shaft Diameter:

0.124 inches

Bushing Length:

0.160 inches

Shaft Length:

0.538 inches

Frequency Rating:

Not rated

Adjustment Device Quantity:

1

Adjustment Device Drive Type:

Shaft

Body Length:

4.010 inches

Shaft Style:

Round, slotted

Individual Section Quantity:

1

Operating Temperature Range:

-30.0/+70.0 degrees celsius

Mounting Facility Quantity:

1

Voltage Rating:

Not rated

Material And Location:

Any acceptable

Surface Treatment And Location:

Any acceptable

Input Impedance Rating:

1.150 kilohms

Output Impedance Rating:

1.150 kilohms

Frequency Bandwidth:

Not rated

Mounting Facility:

Threaded bushing

Attenuation In Decibels:

Not rated

Signal Delay Method:

Inductance

Delay Time Variation Method:

Variable

Section Delay Time:

250.000 nanoseconds single section err-100

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

40.0 nanoseconds

Terminal Type And Quantity:

4 solder stud

Special Features:

With 0.250-32 thd bushing at read of case

Test Data Document:

64959-g327176revc drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Size And Series/type Designator:

0.250-32 unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100