NSN 5999-00-897-6250

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-897-6250 **Thread Class:** Any acceptable **Thread Pitch Diameters:** Any acceptable **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 2.375 inches **Body Width:** 2.250 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** Any acceptable **Operating Tempurature Range:** Not rated **Mounting Facility Quantity: Voltage Rating:** Not rated **Material And Location:** Any acceptable **Surface Treatment And Location:** Any acceptable Input Impedance Rating: Not rated **Output Impedance Rating:** Not rated Frequency Bandwidth: Not rated **Body Depth:** 1.250 inches **Mounting Facility:** Threaded hole **Mounting Provision Arrangement Style:** 2 position in-line **Attenuation In Decibels:** Not rated

Signal Delay Method: Lumped constant

NSN 5999-00-897-6250

Delay Line - Page 2 of 2



Section Delay Time:
600.000 nanoseconds single section
Segment Quantity Per Section:
Any acceptable
Segment Delay Time:
Any acceptable
Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
Not rated
Terminal Type And Quantity:
6 wire leads
Thread Size And Series/type Designator:
Any acceptable
Fsc Application Data:
Radio set
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A32100