NSN 5999-00-899-0803



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-899-0803 **Thread Class:** 2a **Body Style:** Rectangular **Body Length:** 6.202 inches **Body Width:** 3.031 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 2.250 inches **Longest Vertical Distance Between Mounting Centers:** 5.250 inches Stud Length: 0.468 inches **Mounting Facility Quantity: Voltage Rating:** 500.000 volts **Material And Location:** Steel **Surface Treatment And Location:** Tin plated, mil-t-10727, type 1 terminal Input Impedance Rating: 220.000 ohms **Output Impedance Rating:** 220.000 ohms **Body Depth:** 2.031 inches **Mounting Facility:** Threaded stud **Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** 6.000 **Signal Delay Method:** Electromechanical **Section Delay Time:**

33.500 microseconds single section Pulse Rise Time Rating:

1.0 microseconds

NSN 5999-00-899-0803

Delay Line - Page 2 of 2



Terminal Type And Quantity:
3 wire hook
Thread Size And Series/type Designator:
0.164-32 unc
Fsc Application Data:
Radar set, guided missile
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A32100