## NSN 5999-00-900-8895

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-900-8895

Body Style:
Rectangular
Slot Length:
0.312 inches
Frequency Rating:
Not rated
Body Length:
8.531 inches
Body Width:
1.125 inches
Individual Section Quantity:
1
Operating Tempurature Range:
-30.0/+85.0 degrees celsius
Mounting Facility Quantity:
1
Voltage Rating:
Not rated
Material And Location:
Plastic body
Input Impedance Rating:
5.500 kilohms
Output Impedance Rating:
5.500 kilohms
Frequency Bandwidth:
Not rated
Body Depth:
0.562 inches
Mounting Facility:
Slotted hole
Attenuation In Decibels:
3.000
Signal Delay Method:
Lumped constant
Delay Time Variation Method:
Tapped
Section Delay Time:
22.000 microseconds single section
Segment Quantity Per Section:
3 single section
Segment Delay Time:

8.500 microseconds single section 2nd segment err-100

# NSN 5999-00-900-8895

Delay Line - Page 2 of 2



Delay Time Variation Per Deg Celsius:

Not rated

## Pulse Rise Time Rating:

1.8 microseconds

## Terminal Type And Quantity:

5 turret

#### Err Default:

Err default

#### Fsc Application Data:

Radar nonairborne except fire control and guided missile

Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

#### Fiig:

A32100