## NSN 5999-00-904-1566



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-904-1566 **Thread Class:** 2b **Body Style:** Rectangular **Body Length:** 4.000 inches **Body Width:** 2.250 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 1.500 inches **Longest Vertical Distance Between Mounting Centers:** 3.250 inches **Operating Tempurature Range:** +0.0/+65.0 degrees celsius **Mounting Facility Quantity:** 4 **Voltage Rating:** 50.000 volts Input Impedance Rating: 50.000 ohms **Output Impedance Rating:** 50.000 ohms Frequency Bandwidth: 24000.0 kilohertz **Body Depth:** 0.600 inches **Mounting Facility:** Threaded hole **Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** 1.000 **Section Delay Time:** 450.000 nanoseconds single section **Segment Quantity Per Section:** 10 single section

Segment Delay Time: 45.000 nanoseconds s

45.000 nanoseconds single section all segments

**Pulse Rise Time Rating:** 

15.0 nanoseconds

## NSN 5999-00-904-1566

Delay Line - Page 2 of 2



Terminal Type And Quantity	Terminal	<b>Type</b>	And	Quantity	<b>/</b> :
----------------------------	----------	-------------	-----	----------	------------

12 solder stud

Thread Size And Series/type Designator:

0.112-40 unc

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

Yes - demil/mli

Fiig:

A32100