NSN 5999-00-906-1962

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-906-1962

Body Style:
Rectangular
Frequency Rating:
Between 22.000 kilohertz and 34.000 kilohertz
Body Length:
6.000 inches
Body Width:
1.500 inches
Individual Section Quantity:
1
Longest Horizontal Distance Between Mounting Centers:
5.000 inches
Longest Vertical Distance Between Mounting Centers:
1.000 inches
Mounting Facility Quantity:
4
Input Impedance Rating:
2.500 kilohms
Output Impedance Rating:
2.500 kilohms
Body Depth:
2.500 inches
Mounting Facility:
Unthreaded hole
Mounting Provision Arrangement Style:
Four position rectangular
Attenuation In Decibels:
1.000
Delay Time Variation Method:
Tapped
Section Delay Time:
67.300 microseconds single section
Segment Quantity Per Section:
10 single section
Segment Delay Time:
65.700 microseconds single section 2nd segment err-100
Terminal Type And Quantity:
13 wire hook
Thread Size And Series/type Designator:
0.138-32 unc
Shelf Life:
N/o

NSN 5999-00-906-1962

Delay Line - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100