

View Online at <https://aerobasegroup.com/nsn/5999-00-906-1967>

**Thread Class:**

2a

**Body Style:**

Rectangular

**Frequency Rating:**

Not rated

**Body Length:**

7.500 inches

**Body Width:**

3.000 inches

**Individual Section Quantity:**

3

**Longest Horizontal Distance Between Mounting Centers:**

6.750 inches

**Longest Vertical Distance Between Mounting Centers:**

2.250 inches

**Operating Temperature Range:**

+0.0/+50.0 degrees celsius

**Stud Length:**

0.375 inches

**Mounting Facility Quantity:**

4

**Voltage Rating:**

Not rated

**Material And Location:**

Metal

**Surface Treatment And Location:**

Enamel, mil-e-15090, type 1, class 2 err-100 err-100

**Input Impedance Rating:**

1.000 kilohms

**Output Impedance Rating:**

1.000 kilohms

**Frequency Bandwidth:**

Not rated

**Body Depth:**

3.500 inches

**Mounting Facility:**

Threaded stud

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

12.000

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

1.000 milliseconds all sections

**Segment Quantity Per Section:**

10 all sections

**Segment Delay Time:**

95.000 microseconds all sections all segments err-100

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

Not rated

**Terminal Type And Quantity:**

33 wire hook

**Thread Size And Series/type Designator:**

0.138-32 unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100