

View Online at <https://aerobasegroup.com/nsn/5999-00-906-1967>

Thread Class:

2a

Body Style:

Rectangular

Frequency Rating:

Not rated

Body Length:

7.500 inches

Body Width:

3.000 inches

Individual Section Quantity:

3

Longest Horizontal Distance Between Mounting Centers:

6.750 inches

Longest Vertical Distance Between Mounting Centers:

2.250 inches

Operating Temperature Range:

+0.0/+50.0 degrees celsius

Stud Length:

0.375 inches

Mounting Facility Quantity:

4

Voltage Rating:

Not rated

Material And Location:

Metal

Surface Treatment And Location:

Enamel, mil-e-15090, type 1, class 2 err-100 err-100

Input Impedance Rating:

1.000 kilohms

Output Impedance Rating:

1.000 kilohms

Frequency Bandwidth:

Not rated

Body Depth:

3.500 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

12.000

Delay Time Variation Method:

Tapped

Section Delay Time:

1.000 milliseconds all sections

Segment Quantity Per Section:

10 all sections

Segment Delay Time:

95.000 microseconds all sections all segments err-100

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

Not rated

Terminal Type And Quantity:

33 wire hook

Thread Size And Series/type Designator:

0.138-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100