

View Online at <https://aerobasegroup.com/nsn/5999-00-907-0595>

Thread Class:

2a

Thread Pitch Diameters:

+0.1399/+0.1428 inches

Body Style:

Cylindrical

Body Diameter:

1.656 inches

Frequency Rating:

Not rated

Body Length:

1.125 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.844 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Stud Length:

0.406 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

2

Voltage Rating:

500.000 volts

Input Impedance Rating:

3.200 kilohms

Output Impedance Rating:

3.200 kilohms

Frequency Bandwidth:

Not rated

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

2 position in-line

Attenuation In Decibels:

4.340

Signal Delay Method:

Inductance

Delay Time Variation Method:

Tapped

Section Delay Time:

15.900 microseconds single section

Segment Quantity Per Section:

3 single section

Segment Delay Time:

7.900 microseconds single section 3rd segment err-100

Delay Time Variation Per Deg Celsius:

2.500 microseconds

Pulse Rise Time Rating:

800.0 nanoseconds

Terminal Type And Quantity:

5 wire loop

Thread Size And Series/type Designator:

0.164-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100