NSN 5999-00-916-7948



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-916-7948 **Thread Class:** 2a **Thread Pitch Diameters:** +0.1257/+0.1437 inches **Body Style:** Cylindrical **Body Diameter:** 1.656 inches Frequency Rating: Not rated **Body Length:** 3.125 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 1.844 inches **Operating Tempurature Range:** Not rated Stud Length: 0.406 inches **Mounting Facility Quantity:** 2 **Voltage Rating:** Not rated **Material And Location:** Any acceptable Input Impedance Rating: 1.200 kilohms **Output Impedance Rating:** 1.200 kilohms Frequency Bandwidth: Not rated **Mounting Facility:** Threaded stud **Mounting Provision Arrangement Style:** 2 position in-line **Attenuation In Decibels:** Not rated **Signal Delay Method:**

Inductance
Section Delay Time:

950.000 nanoseconds 2nd section err-100

NSN 5999-00-916-7948Delay Line - Page 2 of 2



| Delay Time Variation Per Deg Celsius: |
|---|
| Not rated |
| Pulse Rise Time Rating: |
| 200.0 nanoseconds |
| Terminal Type And Quantity: |
| 4 wire hook |
| Thread Size And Series/type Designator: |
| 0.164-32 unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

Fiig: A32100