## NSN 5999-00-922-2974



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-922-2974 **Body Style:** Rectangular Frequency Rating: Not rated **Adjustment Device Drive Type:** Linear slide **Body Length:** 4.660 inches **Body Width:** 1.030 inches **Individual Section Quantity:** 2 **Longest Horizontal Distance Between Mounting Centers:** 4.406 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Mounting Facility Quantity:** 2 **Voltage Rating:** Not rated Input Impedance Rating: 300.000 ohms **Output Impedance Rating:** 300.000 ohms Frequency Bandwidth: Not rated **Body Depth:** 0.440 inches **Mounting Facility:** Unthreaded hole **Mounting Provision Arrangement Style:** 2 position in-line **Attenuation In Decibels:** Not rated **Signal Delay Method:** Lumped constant **Delay Time Variation Method:** Variable **Section Delay Time:** 

8.000 microseconds all sections

**Delay Time Variation Per Deg Celsius:** 

Not rated

## NSN 5999-00-922-2974

Delay Line - Page 2 of 2



Pu	lse	Rise	Time	Rating	1:

Not rated

**Terminal Type And Quantity:** 

6 tab solder lug

**Fsc Application Data:** 

Transponder set, identification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100