

View Online at <https://aerobasegroup.com/nsn/5999-00-922-5989>

Thread Class:

2b

Body Style:

Rectangular

Frequency Rating:

16.500 kilohertz

Adjustment Device Drive Type:

Slotted screw

Body Length:

3.942 inches

Body Width:

3.255 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

2.700 inches

Longest Vertical Distance Between Mounting Centers:

2.500 inches

Operating Temperature Range:

+0.0/+60.0 degrees celsius

Mounting Facility Quantity:

4

Voltage Rating:

20.000 volts

Material And Location:

Any acceptable

Surface Treatment And Location:

Any acceptable

Input Impedance Rating:

500.000 ohms

Output Impedance Rating:

1.500 kilohms

Frequency Bandwidth:

400.0 kilohertz

Body Depth:

0.460 inches

Mounting Facility:

Threaded hole

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

Not rated

Signal Delay Method:

Inductance

Delay Time Variation Method:

Variable

Section Delay Time:

83.900 microseconds single section

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

150.0 nanoseconds

Terminal Type And Quantity:

5 solder stud

Test Data Document:

10001-2557873 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Size And Series/type Designator:

0.138-32 unc

Fsc Application Data:

Radar sets, fire control nonairborne

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100