

View Online at <https://aerobasegroup.com/nsn/5999-00-923-4600>

Thread Class:

2a

Body Style:

Rectangular

Body Length:

6.250 inches

Body Width:

3.000 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

5.562 inches

Longest Vertical Distance Between Mounting Centers:

2.343 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Stud Length:

0.470 inches

Mounting Facility Quantity:

4

Material And Location:

Steel case

Surface Treatment And Location:

Any acceptable

Input Impedance Rating:

500.000 ohms

Output Impedance Rating:

500.000 ohms

Frequency Bandwidth:

17.0 kilohertz

Body Depth:

3.000 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

1.000

Signal Delay Method:

Inductance

Delay Time Variation Method:

Tapped

Section Delay Time:

500.000 microseconds single section

Segment Quantity Per Section:

100 single section

Segment Delay Time:

5.000 microseconds single section all segments

Terminal Type And Quantity:

20 wire hook

Test Data Document:

10001-2423821 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Size And Series/type Designator:

0.190-32 unf

Fsc Application Data:

Fire control sonar equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100