NSN 5999-00-932-1316



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-932-1316 **Body Style:** Rectangular **Body Length:** 2.030 inches **Body Width:** 0.600 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 1.600 inches **Shortest Horizontal Distance Between Mounting Centers:** 0.200 inches **Intermediate Horizontal Distance Between Mounting Centers:** 0.600 inches **Mounting Facility Quantity: Material And Location:** Any acceptable **Surface Treatment And Location:** Any acceptable Input Impedance Rating: 500.000 ohms **Output Impedance Rating:** 500.000 ohms Frequency Bandwidth: 7200.0 kilohertz **Body Depth:** 0.420 inches **Mounting Facility: Terminal Mounting Provision Arrangement Style:** Four position off-set **Signal Delay Method:** Inductance **Delay Time Variation Method: Tapped Section Delay Time:** 400.000 nanoseconds single section

Segment Quantity Per Section:

1 single section

Segment Delay Time:

100.000 nanoseconds single section 1st segment

NSN 5999-00-932-1316

Delay Line - Page 2 of 2



Pu	lse	Rise	Time	Rating	1:

50.0 nanoseconds

Terminal Type And Quantity:

4 pin

Fsc Application Data:

Guided missile component

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100