

View Online at <https://aerobasegroup.com/nsn/5999-00-932-1316>

Body Style:

Rectangular

Body Length:

2.030 inches

Body Width:

0.600 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.600 inches

Shortest Horizontal Distance Between Mounting Centers:

0.200 inches

Intermediate Horizontal Distance Between Mounting Centers:

0.600 inches

Mounting Facility Quantity:

4

Material And Location:

Any acceptable

Surface Treatment And Location:

Any acceptable

Input Impedance Rating:

500.000 ohms

Output Impedance Rating:

500.000 ohms

Frequency Bandwidth:

7200.0 kilohertz

Body Depth:

0.420 inches

Mounting Facility:

Terminal

Mounting Provision Arrangement Style:

Four position off-set

Signal Delay Method:

Inductance

Delay Time Variation Method:

Tapped

Section Delay Time:

400.000 nanoseconds single section

Segment Quantity Per Section:

1 single section

Segment Delay Time:

100.000 nanoseconds single section 1st segment

Pulse Rise Time Rating:

50.0 nanoseconds

Terminal Type And Quantity:

4 pin

Fsc Application Data:

Guided missile component

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100