NSN 5999-00-933-4878

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-933-4878 **Thread Class: Thread Pitch Diameters:** Any acceptable **Body Style:** Rectangular **Body Length:** 8.000 inches **Body Width:** 7.000 inches **Individual Section Quantity: Operating Tempurature Range:** +0.0/+55.0 degrees celsius **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity:** 4 **Voltage Rating:** Between 4.500 volts and 5.500 volts **Material And Location:** Steel case **Surface Treatment And Location:** Enamel, mil-e-15090, type 2, class 2 case Input Impedance Rating: Not rated **Output Impedance Rating:** Not rated Frequency Bandwidth: Not rated **Body Depth:** 2.000 inches **Mounting Facility:** Threaded hole **Attenuation In Decibels:**

Not rated **Signal Delay Method:** Magnetostriction **Section Delay Time:** 2500.000 microseconds single section **Delay Time Variation Per Deg Celsius:** 0.500 microseconds

NSN 5999-00-933-4878Delay Line - Page 2 of 2



Pulse Rise Time Rating:
0.1 microseconds
Terminal Type And Quantity:
6 wire hook
Thread Size And Series/type Designator:
Any acceptable
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A32100