# NSN 5999-00-933-4878

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-933-4878

Thread	Class:

1a

- **Thread Pitch Diameters:**
- Any acceptable

## Body Style:

Rectangular

## **Body Length:**

8.000 inches

### **Body Width:**

7.000 inches

## Individual Section Quantity:

1

#### **Operating Tempurature Range:**

+0.0/+55.0 degrees celsius

#### Inclosure Type:

## Hermetically sealed

#### **Mounting Facility Quantity:**

4

## Voltage Rating:

Between 4.500 volts and 5.500 volts

### Material And Location:

Steel case

#### Surface Treatment And Location:

Enamel, mil-e-15090, type 2, class 2 case

### Input Impedance Rating:

Not rated

#### **Output Impedance Rating:**

Not rated

#### Frequency Bandwidth:

Not rated

#### Body Depth:

2.000 inches

#### **Mounting Facility:**

Threaded hole

#### Attenuation In Decibels:

Not rated

### Signal Delay Method:

Magnetostriction

### Section Delay Time:

2500.000 microseconds single section

# Delay Time Variation Per Deg Celsius:

0.500 microseconds

# NSN 5999-00-933-4878

Delay Line - Page 2 of 2



# Pulse Rise Time Rating:

0.1 microseconds

# Terminal Type And Quantity:

6 wire hook

# Thread Size And Series/type Designator:

Any acceptable

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

Yes - demil/mli

#### Fiig:

A32100