

View Online at <https://aerobasegroup.com/nsn/5999-00-936-7268>

Thread Class:

2a

Thread Pitch Diameters:

+0.1140/+0.1160 inches

Body Style:

Rectangular

Frequency Rating:

Not rated

Body Length:

3.370 inches

Body Width:

1.020 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.340 inches

Longest Vertical Distance Between Mounting Centers:

2.910 inches

Operating Temperature Range:

-54.0/+125.0 degrees celsius

Stud Length:

0.340 inches

Mounting Facility Quantity:

2

Voltage Rating:

Not rated

Material And Location:

Any acceptable

Surface Treatment And Location:

Any acceptable

Input Impedance Rating:

1.200 kilohms

Output Impedance Rating:

1.200 kilohms

Frequency Bandwidth:

Not rated

Body Depth:

0.770 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

2 position diagonal

Attenuation In Decibels:

Not rated

Signal Delay Method:

Lumped constant

Section Delay Time:

34.200 microseconds single section

Segment Quantity Per Section:

4 single section

Segment Delay Time:

12.000 microseconds single section 4th segment err-100

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

3.0 microseconds

Terminal Type And Quantity:

5 solder stud

Thread Size And Series/type Designator:

0.138-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100