

View Online at <https://aerobasegroup.com/nsn/5999-00-938-1550>

Body Style:

Rectangular, bracketed

Hole Diameter:

0.250 inches

Overall Length:

Between 4.344 inches and 4.406 inches

Frequency Rating:

Between 500.000 hertz and 700.000 hertz

Body Length:

3.625 inches

Body Width:

3.250 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.000 inches

Operating Temperature Range:

-5.0/+85.0 degrees celsius

Mounting Facility Quantity:

1 and 2

Voltage Rating:

2.000 volts

Material And Location:

Beryllium copper alloy, qq-c-530, cond 1/2 hard terminal err-100 err-100

Surface Treatment And Location:

Paint, zinc chromate primer, jan-p-735 fscm 81349 body

Input Impedance Rating:

20.000 kilohms

Output Impedance Rating:

2.000 kilohms

Frequency Bandwidth:

6.5 kilohertz

Body Depth:

1.625 inches

Mounting Facility:

Bracket and unthreaded hole

Mounting Provision Arrangement Style:

2 position in-line

Attenuation In Decibels:

44.500

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

319.300 microseconds single section

Segment Quantity Per Section:

7 single section

Segment Delay Time:

81.800 microseconds single section 1st segment err-100

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

Not rated

Terminal Type And Quantity:

18 pin

Special Features:

Hermetically sealed case

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100